

## Issues

| #  | Project       | Tracker | Status | Priority | Subject  | Assignee | Updated          | Estimated time | % Done |
|----|---------------|---------|--------|----------|--|----------|------------------|----------------|--------|
| 4  | mrtg treeview | Feature | New    | Normal   | Documentation  |          | 2011-05-22 10:51 |                | 0      |
| 2  | mrtg treeview | Bug     | New    | Normal   | Changing the list also resets the timespan                         |          | 2008-04-13 12:30 |                | 0      |
| 51 | wconsd        | Feature | New    | Normal   | Encrypted communications   |          | 2008-07-12 21:03 |                | 0      |
| 50 | wconsd        | Feature | New    | Normal   | Configuration file   |          | 2008-07-12 21:02 |                | 0      |
| 49 | wconsd        | Feature | New    | Normal   | Cisco compatible commandline processor                             |          | 2008-07-12 21:00 |                | 0      |
| 32 | wconsd        | Feature | New    | Normal   | Mangle outbound net data to escape special characters              |          | 2008-04-21 19:15 |                | 0      |
| 29 | wconsd        | Feature | New    | Normal   | Stop wconsd via a network command                                  |          | 2008-04-21 00:29 |                | 0      |
| 28 | wconsd        | Bug     | Closed | Normal   | automatic help screens   |          | 2008-05-09 15:47 |                | 0      |
| 27 | wconsd        | Feature | New    | Normal   | redesign internal command processor to be extensible               |          | 2008-04-22 10:29 |                | 0      |
| 26 | wconsd        | Feature | New    | Normal   | list available com ports   |          | 2008-04-23 16:53 |                | 0      |
| 25 | wconsd        | Feature | Closed | Normal   | Full featured command line editing                                 |          | 2008-05-09 15:51 |                | 0      |
| 22 | wconsd        | Feature | New    | Normal   | Visible progress indicators displayed on the console               |          | 2008-04-20 23:48 |                | 0      |
| 21 | wconsd        | Feature | New    | Normal   | Listen port needs to be configurable                               |          | 2008-04-20 23:32 |                | 10     |
| 18 | wconsd        | Bug     | Closed | Normal   | menu interpreter cannot handle receiving CR LF                     |          | 2008-04-18 15:55 |                | 50     |
| 17 | wconsd        | Bug     | Closed | Normal   | No telnet option processing is done                                |          | 2008-04-20 23:34 |                | 80     |
| 31 | wconsd        | Feature | Closed | Normal   | Implement a raw mode that does not mangle any recieved data        |          | 2008-05-15 19:39 |                | 100    |
| 30 | wconsd        | Bug     | Closed | Normal   | Some clients still cause two lines to be seen by the serial device |          | 2008-04-21 19:16 |                | 100    |
| 23 | wconsd        | Feature | Closed | Normal   | Support "send break" sequence                                      |          | 2008-04-22 10:34 |                | 100    |
| 20 | wconsd        | Bug     | Closed | Normal   | cannot return to menu  |          | 2008-04-21 18:46 |                | 100    |
| 19 | wconsd        | Bug     | Closed | Normal   | more than one connection causes wierdness                          |          | 2008-04-21 15:34 |                | 100    |
| 16 | wconsd        | Bug     | Closed | Normal   | Extra line is seen after every enter                               | Hamish   | 2008-04-21 18:46 | 4.00           | 100    |